



H.264 Network DVR

MOTION TRIGGER RECORDING:	YES
RECORDING MODE:	MANUAL / TIMER / MOTION DETECTION
HARD DISK STORAGE:	SUPPORTS UP TO 1.5TB HDD
COMPRESSION FORMAT:	H.264
AUDIO INPUT:	4 AUDIO INPUT, (RCA)
AUDIO OUTPUT:	1 AUDIO OUTPUT. (RCA)
VIDEO FORMAT:(VIDEO SYSTEM)	PAL/NTSC
VIDEO INPUT:	4 CAMERA INPUTS (BNC)
VIDEO OUTPUT:	1 x BNC. 1 x VGA
CAMERA INPUT SIGNAL:	COMPOSITE VIDEO SIGNAL 1.0 VP-P 75Ω BNC
PRIMARY MONITOR OUTPUT:	BNC
SECONDARY MONITOR OUTPUT:	VGA
ADDITIONAL MONITOR OUTPUT:	No
DISPLAY RESOLUTION:	D1 PIXELS
RECORD FRAME RATE/RESOLUTION:	PAL: 25FPS/720x576; 50FPS/720x288; 100FPS/360x288 NTSC: 30FPS/720x480; 60FPS/720x240; 120FPS/360x240
DISPLAY FRAME RATE:	25FPS x 4 (PAL) / 30FPS x 4 (NTSC)
PICTURE IN PICTURE:	No
IMAGE SEQUENCING:	No
MASKING DETECTION AREA:	13 x 10
KEY LOCK:	No
VIDEO ADJUSTABLE:CHROMATICITY/LUMINOSITY/CONTRAST/SATURATION ADJUSTABLE	
VIDEO LOSS DETECTION:	YES
DWELL TIME:	No
CAMERA TITLE:	YES
SIMPLEX/DUPLEX/TRIPLEX OPERATION:	HEXAPLEX
TIME DISPLAY FORMAT:	YY/MM/DD, MM/DD/YY
NETWORK INTERFACE:	YES
COMMUNICATION PORT:	YES

x4 Sony HAD CCD Cameras

IMAGE SENSOR:	1/4-INCH SONY SUPER HAD CCD
SIGNAL SYSTEM:	PAL/NTSC
EFFECTIVE PIXELS:	PAL: 500(H) x 582(V); NTSC: 510(H) x 492(V)
HORIZONTAL RESOLUTION:	420TVL
VIEWING ANGLE:	(BUILT-IN LENS) 6MM (42°)
VIDEO OUTPUT:	1.0 VP-P750
NUMBER OF LEDs:	12 LEDs (UP TO 10M NIGHTVISION)
AUDIO:	No
S/N RATIO:	MORE THAN 48dB(AGC OFF)
GAIN CONTROL:	AUTO
MINIMUM ILLUMINATION: 0 LUX (INFRARED LEDs TURNED ON)	
GAMMA CHARACTERISTIC:	0.45
SHUTTER SPEED:	1/50(1/60)-1/100.000 SEC
INDOOR USE:	YES
OUTDOOR USE:	YES
POWER CONSUMPTION:	12VDC, 120MA (WHEN THE INFRARED LAMPS TURN ON 300MA)

Whats in the Box

- H.264 NETWORK DVR
- 4 x SONY CCD NIGHTVISION WEATHERPROOF CAMERAS
- USB MOUSE
- REMOTE CONTROL
- SOFTWARE CD
- POWER ADAPTOR
- 1 IN 4 POWER SPLITTER CABLE
- 4 x BNC 18.3M "SHOTGUN" CABLE
- INSTRUCTION MANUAL