

Vandal-proof / Mini Dome Camera



Features


- Sony Super HAD CCD sensor
- Built-in Board Lens
- DC voltage





• Vandal-proof




• Normal mini



Vandal-proof



Normal mini



Model No.	IV-D301	IV-D302	IV-D401
	Normal mini	Normal mini	Vandal proof
Image Device	1/4" Colour Sony Super HAD	1/3" Colour Sony Super HAD (Hi-Res.)	1/3" Colour Sony Super HAD (Hi-Res.)
Picture Elements	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582	NTSC:768x494, PAL:752x582
Resolution	420 TVL	520 TVL	520 TVL
Min. Illumination	0.5 Lux / F2.0	0.3 Lux / F2.0	0.3 Lux / F2.0
S/N Ratio	More than 48dB		
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000		
Gamma	0.45		
Lens Furnished	Board Lens 3.6mm / F2.0 (option:2.5/4.3/6/8/12/16mm)		
White Balance	Auto		
Gain Control	Auto		
Sync. System	Internal		
Video Output	1 Vp-p / 75 Ohms		
Audio Output	2 Vp-p / 50 Ohms (option, for RYK-2311/2385/3341/3343)		
Power Supply	DC12V±10%		
Power Consumption	117mA max.	110mA max.	
Operating Temp.	-10°C ~ 50°C		